



MONITOR™

Direct Vent Room Heaters for Natural Gas or Liquid Propane



GF3800

GF1800

**Keeping America's Homes
Warm Since 1984**

Using Technology To Save You Money!



MONITOR™

Safety and Cost Saving!

Monitor owners consider their Monitor Heaters as one of their most prized possessions. And why not? The Monitor looks good in your home, while also being economical, reliable, clean and safe. The Monitor maintains a steady temperature, without the inefficient temperature swings commonly found in some of the other brands of room heaters. Temperature control is vital for efficient heat management, fuel savings and reduced emissions. The heat emitted is circulated around the home by a circulation fan. The Monitor Heaters can heat up rooms very quickly and are independently controlled. The air required for combustion is drawn in from outside and the combustion gases are also discharged outside.

With the freestanding GF series gas heaters you can program four different times and four different temperatures to match the activities of your family. The GF series each have a 7-day timer, so you can customize the four time/temperature settings for individual days of the week. When using the Economy Plus mode you will reduce the already low electrical consumption, prolong component life, and increase the Monitor's efficiency.



GF Series Key Features

Multiple Heat Exchanger: Extracts 83% energy efficient.

Dual Blowers: Separate fans for combustion and room air circulation

Thermostatically Controlled: Adjusts to the desired room temperature

Child Lock: Prevents accidental operation by curious children

Indicator Lights: Easy-to-see signals show when heater is in operation, when timer is activated, and when the burner is operating, or when child lock is engaged

Memory Backup: Heat will automatically resume operation after power is restored

Easy Installation: Includes all parts required for a standard installation

Direct Vent Room Heaters For Natural Gas or Liquid Propane



GF3800

Safety Features



- **Electrical Protection:** Heater automatically shuts off in the unlikely event of a malfunction in the electrical circuitry or disruption of the power supply
- **No Exhaust in Room:** Produced combustion are discharged outdoors
- **Flue Pipe:** Outside air is drawn through a pipe-within-a pipe venting system. This process preheats combustion air regaining heat from exhaust gases

Specifications

		GF3800		GF1800	
		Natural gas	LP	Natural gas	LP
Input Rating (Btu/hour)	High	38,000	34,500	20,000	20,000
	Low	21,600	21,600	12,600	13,400
Output Rating (Btu/hour)	High	30,700	27,900	16,000	16,000
	Low	17,500	17,500	10,200	10,900
Annual Fuel Utilization Efficiency (AFUE)		83%	83%	83%	83%
Dual Blowers		yes		yes	
Timer		4 Times, 4 Temperatures, 7 Days		4 Times, 4 Temperatures, 7 Days	
Digital Control Panel		yes		yes	
Dimensions	Height	26.6		26	
	Width	28.7		20.9	
	Depth	14.0		13.0	
Weight		82 lbs.		55 lbs.	
Warranty		2 years plus add. 36 month for heat exchanger and combustion chamber			

Monitor Products, Inc.

7A Marlen Drive
 Robbinsville, NJ 08691
 Toll free (800) 524-1102
 Phone (609) 584-0505
 Fax (609) 584-7629
 www.monitorproducts.com
 e-mail: info@monitorproducts.com

